

S40 Series



ONE-HAND OPERATION, GENERAL PURPOSE COUPLINGS

SafeWay's S40 Series is a general purpose, double shut-off fluid transfer quick coupling available with either a rugged ball valve or leak-free, high flow poppet valve. The S40 was the first two-way (double acting) sleeve quick coupling, introduced by SafeWay in 1969 as our first product. The S40 Series is widely used wherever the ease and convenience of one-hand connection or disconnection is desired. It is original equipment on a wide variety of agricultural and mobile equipment.



- 1/2" body size meets dimensional requirements of International Standard 5675.
- Two-way, double acting sleeve of the S40 Series allows one-hand connect or disconnect when the coupling is clamp or bulkhead mounted.
- Available in body sizes from 1/4" to 1/2", in a variety of thread sizes and styles.
- Double shut-off design available with either a rugged ball valve or leak-free, high flow poppet valve.
- Reliable and durable ball locking mechanism provides smooth operation time after time.
- Critical parts are hardened for long service life.
- Two-way sleeve design allows implement break-away when the coupling is clamp or bulkhead mounted.
- Interchangeable half-for-half with the Parker/Pioneer 4200 Series.
- All poppet valve models are 100% leak tested before leaving the factory.
- Heavy-duty dust plugs and dust caps available.
- Heavy-duty double break-away clamp available.
- Heavy-duty snap-rings for bulkhead mounting available.
- Method of obtaining and presenting performance data conforms to ANSI/(NFPA)T3.20.2.R2, *Hydraulic fluid power - Quick-action couplings - Test methods.*

PERFORMANCE DATA

PART NUMBERS					OPERATING PRESSURE		RATED FLOW	
Complete Coupler	Female Body Half	Male Tip Half	Body Size	Thread Size and Description	Maximum		GPM	(LPM)
					PSI	(BAR)		
S40-2	S45-2	S41-2	1/4"	1/4" Female Pipe	3,000	(207)	3	(12)
S40-2P	S45-2P	S41-2P	1/4"	1/4" Female Pipe	3,000	(207)	3	(12)
S40-3	S45-3	S41-3	3/8"	3/8" Female Pipe	3,000	(207)	6	(23)
S40-3P	S45-3P	S41-3P	3/8"	3/8" Female Pipe	3,000	(276)	6	(23)
S40-3P-BSP	S45-3P-BSP	S41-3P-BSP	3/8"	G 3/8" BSP Female	3,000	(207)	6	(23)
S40-36	S45-36	S41-36	3/8"	M16-1.5 Female Metric	3,000	(207)	6	(23)
S40-36P	S45-36P	S41-36P	3/8"	M16-1.5 Female Metric	3,000	(207)	6	(23)
S40-4	S45-4	S71-4	1/2"	1/2" Female Pipe	3,000	(207)	12	(45)
S40-4P	S45-4P	S71-4P	1/2"	1/2" Female Pipe	3,000	(207)	12	(45)
S40-4P-BSP	S45-4P-BSP	S561-4-BSP	1/2"	G 1/2" BSP Female	4,000	(276)	12	(45)
S40-15	S45-15	S71-15	1/2"	3/4"-16 Female ORB	3,000	(207)	12	(45)
S40-15P	S45-15P	S71-15P	1/2"	3/4"-16 Female ORB	3,000	(207)	12	(45)
S40-6	S45-6	S71-6	1/2"	3/4" Female Pipe	3,000	(207)	12	(45)
S40-6P	S45-6P	S71-6P	1/2"	3/4" Female Pipe	3,000	(207)	12	(45)

Temperature Range: Standard Seals (Buna-N) -40° to +250° F Viton® Option -15° to +450° F Other Seals Available.
 Vacuum Data: 27.4 inches Hg, both connected and disconnected – Poppet valved models in all sizes (P suffix).

Viton® is a registered trademark of DuPont Dow Elastomers.

Pressure rating (Max. Operating Pressure) is based on Non-Pulsating, Low Cycle applications with essentially steady pressure during the operating cycle. Please consult factory regarding other applications.

